

Construction products regulation Declaration of performance

Product Identification:	Multipanel® Linda Barker, Heritage and Classic Collections
Type:	All standard grades
Intended use:	Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
Company:	Grant Westfield Ltd Westfield Avenue Edinburgh United Kingdom EH11 2QH
System of Assessment and Verification of Constancy of Performance (AVCP):	System 4
Provisions:	EN 13986:2004 Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
	EN 636-2:1997 Plywood for use in humid conditions EN 438-3:2005
	High-pressure decorative laminates (HPL). Sheets based on thermosetting resins (usually called laminates). Classification and specifications for laminates less than 2mm thick intended for bonding to supporting substrates

Essential characteristics	Performance
Bending Strength	EN 636-2
Bonding Quality	EN 314-2 Class 2
Durability (swelling in thickness)	EN 636-2
Durability (Moisture resistance)	EN 636-2
Reaction to Fire	EN 636, 400kg/m3, >9mm: D-s2, d0 When mounted without an airgap
Water Vapour Permeability	70 wet / 200 dry
Formaldehyde	E1
Airborne Sound Insulation	NPD
Sound absorption	0.10 0.30
Thermal Conductivity	0.13 W/m.°K

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

The declaration of performance is issued under the sole responsibility of Grant Westfield Ltd.

Signed for and on behalf of Grant Westfield Ltd by:

Sarah McLean, Managing Director



