## **DUL 1/2 C**

# DU LEVER Tap Range Design Utility Lever Basin Taps Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	1/2"BSP			
Connection Outlet:	M16 Flow Straightener			
Number of Tap Holes:	2			
Valve/Cartridge Type:	1/2" Ceramic Disc Valve - 1/4 turn			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Isolation Included:	No			

#### Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability

#### Product Certifications:



WRAS Certificate No: 1703001 WRAS Expiry Date: 31/03/2022






For more products, visit our website: http://www.bristan.com



#### Dimensions (measurements in mm)



Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
DUL 1/2 C (Cold)	8.5	13.4	18.9	26.8	32.8	42.3		
DUL 1/2 C (Hot)	8.5	13.4	18.9	26.8	32.8	42.3		

### TECHNICAL DATA SHEET



